
xlref Documentation

Release 1.2.4

Vincenzo Arcidiacono

Feb 27, 2024

TABLE OF CONTENTS

1	About xlfref	3
2	Installation	5
3	Reference Syntax	7
4	Tutorial	9
5	Contributing to xlfref	11
6	Donate	13
7	API Reference	15
8	Changelog	27
9	Indices and tables	31
	Python Module Index	33
	Index	35

2024-02-27 15:30:00

<https://github.com/vinci1it2000/xlref>

<https://pypi.org/project/xlref/>

<http://xlref.readthedocs.io/>

<https://github.com/vinci1it2000/xlref/wiki/>

<http://github.com/vinci1it2000/xlref/releases/>

<https://donorbox.org/xlref>

data, excel, tables, parser, reference, ranges

- Vincenzo Arcidiacono <vinci1it2000@gmail.com>

EUPL 1.1+

ABOUT XLREF

xlref is an useful library to capture by a simple reference (e.g., *AI(RD):...:RD*) a table with non-empty cells from Excel-sheets when its exact position is not known beforehand.

This code was inspired by the *xleash* module of the [pandalone](#) library. The reason of developing a similar tool was to have a smaller library to install and improve the performances of reading *.xlsx* files.

INSTALLATION

To install it use (with root privileges):

```
$ pip install xlref
```

Or download the last git version and use (with root privileges):

```
$ python setup.py install
```


REFERENCE SYNTAX


The *capturing* is preformed according to an excel like reference syntax and the non-empty cells of the targeted excel-sheet. The syntax is defined as follows:

```
[<excel>]#[<sheet>!]<st-cel>[(<moves>)][:<nd-cel>[(<moves>)]][:<expansion>][<filters>]
```

Note: The fields between square parenthesis are optional.

Follows the description of the parameters:

- **excel:** excel file path relative to the parent reference file directory. If not defined, the parent reference excel is inherited.
- **sheet:** excel sheet name if not defined, the parent reference excel sheet name is inherited.
- **st-cel:** first cell coordinate of excel range. The cell coordinate (i.e., *<column><row>*) is defined by a column (letter) and row (number), like in excel. *xlref* allows two special characters ^ and _, that represents the leftmost/topmost and rightmost/bottommost non-empty cell column/row.
- **moves:** the sequence of primitive directions (i.e., *L*:left, *U*: up, *R*: right, *D*: down) that *xlref* uses iteratively for finding the first non-empty cell. The allowed primitive direction combinations are *L*, *U*, *R*, *D*, *LD*, *LU*, *UL*, *UR*, *RU*, *RD*, *DL*, and *DR*. The following diagram shows the graphically the *moves* from the starting cell *X*:



- **nd-cel:** second cell coordinate of excel range. It has the same syntax of the *st-cel*, but it has an extra special character .. This represents the column or row of the *st-cel* after the application of the *moves*.
- **expansion:** the sequence of primitive directions to expand the captured range.
- **filters:** list of string and or dictionaries that defines the filters to apply iteratively on the captured range.

3.1 Reference Reading Steps

The library performs the following steps to read a reference:

1. Open the excel file or inherits the parent's one,
2. Open the sheet by its name or inherits the parent's one,
3. Set the first range cell,
4. Move the first cell according to the specified *moves* until it finds the first non-empty cell,
5. Set the second range cell or inherits the moved first range cell,
6. Move the second cell like in point 4,
7. Expand the range according to the defined *expansions*,
8. Apply the iteratively the filters on the captured range.

TUTORIAL

A typical example is *capturing* a table with a “header” row and convert into a dictionary. The code below shows how to do it:

```
>>> import xlref as xl
>>> _ref = 'excel.xlsx#ref!A1(RD):RD[%s]'
>>> ref = xl.Ref(_ref % "dict")
>>> ref.range # Captured range.
B2:C28
>>> values = ref.values; values # Captured values.
{...}
>>> values['st-cell-move']
'#D5(RU):H1(DL)'
```

You can notice from the code above that all the values of the dictionary are references. To parse it recursively, there are two options:

1. add the “recursive” filter before the “dict”:

```
>>> values = xl.Ref(_ref % '"recursive", "dict"').values
>>> values['st-cell-move'].tolist()
[[1.0, 2.0, 3.0],
 [4.0, 5.0, 6.0],
 [7.0, 8.0, 9.0]]
```

2. apply a filter onto dictionary’ values using the extra functionality of the “dict” filter:

```
>>> values = xl.Ref(_ref % '{"fun": "dict", "value":"ref"}').values
>>> values['st-cell-move'].tolist()
[[1.0, 2.0, 3.0],
 [4.0, 5.0, 6.0],
 [7.0, 8.0, 9.0]]
```

You have also the possibility to define and use your custom filters as follows:

```
>>> import numpy as np
>>> xl.FILTERS['my-filter'] = lambda parent, x: np.sum(x)
>>> xl.Ref('#D5(RU):H1(DL)["my-filter"]', ref).values
45.0
```

An alternative way is to use directly the methods of the filtered results as follows:

```
>>> xl.Ref('#D5(RU):H1(DL)["sum"]', ref).values  
45.0
```

CONTRIBUTING TO XLREF

If you want to contribute to **xlref** and make it better, your help is very welcome. The contribution should be sent by a *pull request*. Next sections will explain how to implement and submit a new functionality:

- clone the repository
- implement a new functionality
- open a pull request

5.1 Clone the repository

The first step to contribute to **xlref** is to clone the repository:

- Create a personal [fork](#) of the [xlref](#) repository on Github.
- [Clone](#) the fork on your local machine. Your remote repo on Github is called `origin`.
- [Add](#) the original repository as a remote called `upstream`, to maintain updated your fork.
- If you created your fork a while ago be sure to pull `upstream` changes into your local repository.
- Create a new branch to work on! Branch from `dev`.

5.2 How to implement a new functionality

Test cases are very important. This library uses a data-driven testing approach. To implement a new function I recommend the [test-driven development cycle](#). Hence, when you think that the code is ready, add new test in `test` folder.

When all test cases are ok (`python setup.py test`), open a pull request.

Note: A pull request without new test case will not be taken into consideration.

5.3 How to open a pull request

Well done! Your contribution is ready to be submitted:

- Squash your commits into a single commit with git’s [interactive rebase](#). Create a new branch if necessary. Always write your commit messages in the present tense. Your commit message should describe what the commit, when applied, does to the code – not what you did to the code.
- [Push](#) your branch to your fork on Github (i.e., `git push origin dev`).
- From your fork [open](#) a *pull request* in the correct branch. Target the project’s dev branch!
- Once the *pull request* is approved and merged you can pull the changes from `upstream` to your local repo and delete your extra branch(es).

DONATE

If you want to [support](#) the **xlref** development please donate.

API REFERENCE

The core of the library is composed from the following modules: It contains a comprehensive list of all modules and classes within xlrref.

Docstrings should provide sufficient understanding for any individual function.

Modules:

<i>cli</i>	Define the command line interface.
<i>errors</i>	Defines the xlrref exceptions.
<i>filters</i>	It provides functions implementations to filter the parsed data.
<i>parser</i>	It provides xlrref reference parser class.
<i>process</i>	Defines the file processing chain model <i>dsp</i> .

7.1 cli

Define the command line interface.

7.1.1 xlrref

xlrref command line tool.

```
xlrref [OPTIONS] COMMAND [ARGS]...
```

Options

--version

Show the version and exit.

read

Read recursively the list of xlref data excel references.

OUTPUT_FILE: output file (format: .json).

INPUT_REFERENCE: xlref data excel reference.

```
xlref read [OPTIONS] OUTPUT_FILE [INPUT_REFERENCE] ...
```

Options

-F, --input-file <input_file>

JSON xlref data excel references.

-v, --verbosity <LVL>

Either CRITICAL, ERROR, WARNING, INFO or DEBUG

Arguments

OUTPUT_FILE

Required argument

INPUT_REFERENCE

Optional argument(s)

7.2 errors

Defines the xlref exceptions.

Exceptions

InvalidReference
InvalidSyntax
NoFullCell
XlParserError

7.2.1 InvalidReference

exception `InvalidReference(*args)`

7.2.2 InvalidSyntax

exception `InvalidSyntax(*args)`

7.2.3 NoFullCell

exception `NoFullCell(*args)`

7.2.4 XlParserError

exception `XlParserError(*args)`

7.3 filters

It provides functions implementations to filter the parsed data.

Functions

<i>fdict</i>	Convert the input array into a dictionary.
<i>full</i>	Remove the empty value from each row of the input array.
<i>recursive</i>	Parse recursively all values in the array.
<i>ref</i>	If the input is a valid reference, returns the captured values otherwise the input.

7.3.1 fdict

fdict(*parent*, *x*, *key=None*, *value=None*)

Convert the input array into a dictionary.

Parameters

- **parent** (`xlref.parser.Ref`) – Parent parser.
- **x** (`list`/`numpy.array`) – Array.
- **key** (`str`/`list`) – Filter applied to keys.
- **value** (`str`/`list`) – Filter applied to values.

Returns

Parsed dictionary.

Return type

`dict`

7.3.2 full

full(*parent*, *x*)

Remove the empty value from each row of the input array.

Parameters

- **parent** (`xlref.parser.Ref`) – Parent parser.
- **x** (`list` / `numpy.array`) – Array.

Returns

Filtered array.

Return type

`list`

7.3.3 recursive

recursive(*parent*, *x*, *dtype=None*)

Parse recursively all values in the array.

Parameters

- **parent** (`xlref.parser.Ref`) – Parent parser.
- **x** (`list` / `numpy.array`) – Array.

Returns

Parsed array.

Return type

`numpy.array`

7.3.4 ref

ref(*parent*, *x*)

If the input is a valid reference, returns the captured values otherwise the input.

Parameters

- **parent** (`xlref.parser.Ref`) – Parent parser.
- **x** (`object`) – Input value.

Returns

If the input is a valid reference, returns the captured values otherwise the input.

Return type

`object`

Classes

FiltersFactory

7.3.5 FiltersFactory

class FiltersFactory

Methods

<code>__init__</code>	
<code>clear</code>	
<code>copy</code>	
<code>fromkeys</code>	Create a new dictionary with keys from iterable and values set to value.
<code>get</code>	Return the value for key if key is in the dictionary, else default.
<code>items</code>	
<code>keys</code>	
<code>pop</code>	If the key is not found, return the default if given; otherwise, raise a KeyError.
<code>popitem</code>	Remove and return a (key, value) pair as a 2-tuple.
<code>setdefault</code>	Insert key with a value of default if key is not in the dictionary.
<code>update</code>	If E is present and has a .keys() method, then does: for k in E: D[k] = E[k] If E is present and lacks a .keys() method, then does: for k, v in E: D[k] = v In either case, this is followed by: for k in F: D[k] = F[k]
<code>values</code>	

`__init__`

FiltersFactory.`__init__`(*args, **kwargs)

clear

`FiltersFactory.clear()` → None. Remove all items from D.

copy

`FiltersFactory.copy()` → a shallow copy of D

fromkeys

`FiltersFactory.fromkeys(value=None, /)`

Create a new dictionary with keys from iterable and values set to value.

get

`FiltersFactory.get(key, default=None, /)`

Return the value for key if key is in the dictionary, else default.

items

`FiltersFactory.items()` → a set-like object providing a view on D's items

keys

`FiltersFactory.keys()` → a set-like object providing a view on D's keys

pop

`FiltersFactory.pop(k[, d])` → v, remove specified key and return the corresponding value.

If the key is not found, return the default if given; otherwise, raise a `KeyError`.

popitem

`FiltersFactory.popitem()`

Remove and return a (key, value) pair as a 2-tuple.

Pairs are returned in LIFO (last-in, first-out) order. Raises `KeyError` if the dict is empty.

setdefault

`FiltersFactory.setdefault(key, default=None, /)`
Insert key with a value of default if key is not in the dictionary.
Return the value for key if key is in the dictionary, else default.

update

`FiltersFactory.update([E, ]**F) → None`. Update D from dict/iterable E and F.
If E is present and has a `.keys()` method, then does: for k in E: D[k] = E[k] If E is present and lacks a `.keys()` method, then does: for k, v in E: D[k] = v In either case, this is followed by: for k in F: D[k] = F[k]

values

`FiltersFactory.values()` → an object providing a view on D's values
`__init__(*args, **kwargs)`

7.4 parser

It provides `xlparser` reference parser class.

Functions

<i>compile_filters</i>

7.4.1 compile_filters

`compile_filters(filters, parent)`

Classes

<i>Range</i>	
<i>Ref</i>	Reference parser

7.4.2 Range

class `Range`(*st_cell*, *nd_cell*)

Methods

<code>__init__</code>
<code>get</code>

`__init__`

`Range.__init__(st_cell, nd_cell)`

`get`

`Range.get()`

`__init__(st_cell, nd_cell)`

7.4.3 Ref

class `Ref`(*ref*, *parent=None*, *cache=None*)

Reference parser

Methods

<code>__init__</code>

`__init__`

`Ref.__init__(ref, parent=None, cache=None)`

`__init__(ref, parent=None, cache=None)`

Attributes

book
full_cells
margins
range
sheet
values

book

property Ref.book

full_cells

property Ref.full_cells

margins

property Ref.margins

range

property Ref.range

sheet

property Ref.sheet

values

property Ref.values

7.5 process

Defines the file processing chain model *dsp*.

Functions

<code>load_json</code>	Load the data excel references from files.
<code>merge_references</code>	Merge data excel references.
<code>read_references</code>	Read recursively the list of data excel references.
<code>save_json</code>	Save data output in an JSON file.

7.5.1 load_json

`load_json(input_fpaths)`

Load the data excel references from files.

Parameters

input_fpaths (*list* [*str*]) – File paths of the json data excel references.

Returns

Data excel references from files.

Return type

tuple

7.5.2 merge_references

`merge_references(input_references=(), file_references=())`

Merge data excel references.

Parameters

- **input_references** (*tuple*) – Data excel references from user.
- **file_references** (*tuple*) – Data excel references from files.

Returns

Full list of data excel references.

Return type

list

7.5.3 read_references

`read_references(references)`

Read recursively the list of data excel references.

Parameters

references (*list*) – Full list of data excel references.

Returns

Data output.

Return type

list

7.5.4 save_json

save_json(*output_fpath*, *data*)

Save data output in an JSON file.

Parameters

- **output_fpath** (*str*) – Output file path.
- **data** (*list*) – Data output.

Returns

File path where output are written.

Return type

str

CHANGELOG

8.1 v1.2.4 (2024-02-27)

8.1.1 Fix

- (parser): Correct engines.

8.2 v1.2.3 (2024-02-22)

8.2.1 Fix

- (parser): Update default reader engine and add macro files.
- (doc): Correct issues links.
- (setup): Correct setup config file.

8.3 v1.2.2 (2023-11-15)

8.3.1 Feat

- (setup): Add missing dependencies.
- (bin): Update publish script.
- (doc): Update copyright.
- (test): Use *unittest* for testing instead *nose*.
- (core): Add support for python 3.10 and 3.11.
- (doc): Add Read the Docs configuration file.

8.3.2 Fix

- (parser): Avoid leaving open file.
- (doc): Remove broken badge.

8.4 v1.2.1 (2022-05-10)

8.4.1 Feat

- (parser): Add open method to open files with custom modules.
- (parser): Add method to read csv files.

8.4.2 Fix

- (tests): Correct test cases.
- (parser): Correct bug when empty table.
- (filters): Remove warning.

8.5 v1.2.0 (2022-01-05)

8.5.1 Feat

- (doc): Update copyright.
- (actions): Replace travis with github actions.
- (test): Add new test cases.
- (cli): Use *simplejson* to dump parsed data.

8.5.2 Fix

- (parser): Correct range expansion when is empty.

8.6 v1.1.2 (2021-05-19)

8.6.1 Feat

- (core): Update build scripts.

8.6.2 Fix

- (parser): Correct file regex.
- (filter): Correct VisibleDeprecationWarning.
- (doc): Correct readme version.

8.7 v1.1.1 (2021-01-04)

8.7.1 Fix

- (doc): Update copyrights.
- (parser): Use *openpyxl* to read excel files instead *xld*.

8.8 v1.1.0 (2020-11-05)

8.8.1 Feat

- (filters): Remove *merge* option in *dict* filter and add list filters for *key* and *value* options.

8.8.2 Fix

- (travis): Correct coverage setting.

8.9 v1.0.1 (2020-11-04)

8.9.1 Feat

- (filters): Add *merge* option in *dict* filter.

8.9.2 Fix

- (parser): Implement case insensitive parser for sheet names.

8.10 v1.0.0 (2020-04-07)

First release.

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

PYTHON MODULE INDEX

X

- [xlref](#), 15
- [xlref.cli](#), 15
- [xlref.errors](#), 16
- [xlref.filters](#), 17
- [xlref.parser](#), 21
- [xlref.process](#), 24

Symbols

[__init__\(\) \(FiltersFactory method\)](#), 21
[__init__\(\) \(Range method\)](#), 22
[__init__\(\) \(Ref method\)](#), 22
 -F
 [xlref-read command line option](#), 16
 --input-file
 [xlref-read command line option](#), 16
 --verbosity
 [xlref-read command line option](#), 16
 --version
 [xlref command line option](#), 15
 -v
 [xlref-read command line option](#), 16

C

[compile_filters\(\) \(in module xlref.parser\)](#), 21

F

[fdict\(\) \(in module xlref.filters\)](#), 17
[FiltersFactory \(class in xlref.filters\)](#), 19
[full\(\) \(in module xlref.filters\)](#), 18

I

INPUT_REFERENCE
 [xlref-read command line option](#), 16

L

[load_json\(\) \(in module xlref.process\)](#), 24

M

[merge_references\(\) \(in module xlref.process\)](#), 24
 module
 [xlref](#), 15
 [xlref.cli](#), 15
 [xlref.errors](#), 16
 [xlref.filters](#), 17
 [xlref.parser](#), 21
 [xlref.process](#), 24

O

OUTPUT_FILE

[xlref-read command line option](#), 16

R

[Range \(class in xlref.parser\)](#), 22
[read_references\(\) \(in module xlref.process\)](#), 24
[recursive\(\) \(in module xlref.filters\)](#), 18
[Ref \(class in xlref.parser\)](#), 22
[ref\(\) \(in module xlref.filters\)](#), 18

S

[save_json\(\) \(in module xlref.process\)](#), 25

X

[xlref](#)
 module, 15
[xlref command line option](#)
 --version, 15
[xlref.cli](#)
 module, 15
[xlref.errors](#)
 module, 16
[xlref.filters](#)
 module, 17
[xlref.parser](#)
 module, 21
[xlref.process](#)
 module, 24
[xlref-read command line option](#)
 -F, 16
 --input-file, 16
 --verbosity, 16
 -v, 16
 INPUT_REFERENCE, 16
 OUTPUT_FILE, 16